

SKYLOTEC - MILAN 2.0 VERTICAL RESCUE KIT



(A)



SKYLOTEC MILAN 2.0 HUB – AGR 2001 - 028 with Rope

STANDARD : DIN EN 1496:2017, DIN EN 341-2A:2011, ANSI Z359.4:2013, MEETS CSA Z259.2.3-1B:2012

This Enables An Accident Victim To Be Lifted Across A short Distance In Order To Release The Victim's Lanyard, After Which The Victim Can Then Be Safety Lowered By Rope [Where The New Housing Design Improve Handling For The Accompanying Super Static Rope]

9.0 Static Rope Fulfils This Requirement Despite Its Diameter Of Only 9 Mm Maximum Rescue Height 500m Speed 0 .9 Meter Per Second Approved For Use Two Person Up To 260 Kg Housing Made Of Mild Air Craft Aluminum

(B)



SKYLOTEC SKA RESCUE ROPE CLAMP (FOR MILAN) (L-0058-SK)

Special RESCUE-grade rope clamp for use in Milan Rescue techniques, along with Skylotec Milan Rescue Descender/Ascender systems. L-0058-SK for catching device for victim to lean out of ageing area and lifting by rescue device millan to release from life

STANDARD : EN 1496, EN 353-2:2002

WEIGHT : 0,67 kg.

MATERIAL : Stainless Steel

(C)



SKYLOTEC EDGE GUARD – H056

Edge Guard to divide and protect the rope

Weight : 0.86 kg

Material : Stainless Steel, Polyamide, Steel

(D)



JAYCO Loops - JSL 225

Loops 25KN this sling has a top stitched eyelet into which any approved carabineer hook selected by user can be hooked due to its construction of 25 kn strength hose strap it can also be fastened on pipes and structural component via a girth hitch knot consequently it is ideal as an attachment sling for any kind of fall equipment.

(E)



JAYCO Oval Steel TW - JSC H6

Oval Steel Tw Lock Carabiner EN 362, EN 12275

(F)



Bag for above Kit

A.B.C. BROTHERS TECH (I) PRIVATE LIMITED

"ABC HOUSE" 14/15, Shivam Estate, Nr. Ujala Circle, B/h. SBI & Deepkamal Bajaj, S. G. Highway, Sarkhej, AHMEDABAD-382210. GUJARAT, INDIA
 ☎ +91 79 2689 0331 / 4 / 9 📠 +91 99099 88233. +91 99099 88198 / 7 / 6 📧 info@abcbrothers.in 🌐 www.abcbrothers.in