












Product Code:

Model: KARAM Restraint Twisted Rope Lanyard

Approvals : EN 354 : 2010

KARAM Restraint Twisted Rope Lanyards are provided with the following features:-

1. They are made up of 12mm dia Polyamide Twisted Rope.
2. The spliced end is protected with a strong transparent covering sleeve. This not only protects the splicing, but also makes the splicing visible for easy inspection prior to use.
3. The loops at the end are protected by an abrasion resistant thimble. This prevents the rope from being damaged by the metallic contact of the connector.
4. The rope also has a colored tracer strand which loses its color in due course of time, to show that the Lanyard is now unfit for further use.
5. Minimum Breaking Strength of 22 kN

Ref. no.	Attachment	Lanyard
PN 201	Both Side Loop	
PN 202	One Side Loop Other side Karabiner PN 112	
PN 203	Both side Karabiner PN 112	
PN 204	One side Loop Other side Hook PN 121	
PN 205	Both Side Hook PN 121	
PN 206N	One Side Loop other side Hook PN 121N	
PN 206(A)	One Side Loop Other side Hook PN 136	
PN 207	One side Karabiner PN 112 Other side Hook PN 121	
PN 208N	One side Karabiner PN 112 Other side Hook PN 131N	
PN 208(A)	One side Karabiner PN 112 Other side Hook PN 136	
PN 209N	One side Karabiner PN 121 Other side Hook PN 131N	
PN 209(A)	One side Karabiner PN 121 Other side Hook PN 136	