




Product Code:
Model: KARAM ENERGY ABSORBER WITH EXPANDABLE LANYARDS

Approvals : EN 355: 2002.

1. These Lanyards are ideal for use in conditions where there are chances of the user tripping over the Lanyard. The Elastic nature of the Lanyard reduces the actual effective length of the Lanyard thereby reducing trip hazards.
2. The Lanyards are made with 44mm wide elasticized webbing incorporated for contracting property.
3. The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector
4. KARAM offers a wide range of Energy Absorbing Webbing Lanyards having different configuration of connectors at the ends.
5. All KARAM Lanyards are also supplied with any other hook on special request
6. Relaxed Length: 1.4m & Expanded Length-2.0m
7. All Lanyards with different combinations of connectors mentioned below are individually certified as per EN 355 : 2002

Elasticized webbing Lanyard with Energy Absorber PN 300	Elasticized webbing Lanyard with Energy Absorber PN 400	Attachment	Lanyard
PN 391	PN 391(S)	Both Side Loop	
PN 392	PN 392(S)	One side Loop Other side Karabiner PN 112	
PN 393	PN 393(S)	Both Side Karabiner PN 112	
PN 394	PN 394(S)	One side Loop Other side Hook PN 121	
PN 395	Not Applicable	Both side Hook PN 121	
PN 396	PN 396(S)	One side Loop Other side Hook PN 131	
PN 396N	PN 396N(S)	One side Loop Other side Hook PN 131N	
PN 396(A)	PN 396(S)(A)	One side Loop Other side Hook PN 136	
PN 397	PN 397(S)	One side Karabiner PN 112 Other side Hook PN 121	
PN 398	PN 398(S)	One side Karabiner PN 112 Other side Hook PN 131	
PN 398N	PN 398N(S)	One side Karabiner PN 112 Other side Hook PN 131N	
PN 398(A)	PN 398(S)(A)	One side Karabiner PN 112 Other side Hook PN 136	
PN 399	Not Applicable	One side Karabiner PN 121 Other side Hook PN 131	
PN 399N	Not Applicable	One side Karabiner PN 121 Other side Hook PN 131N	
PN 399(A)	Not Applicable	One side Karabiner PN 121 Other side Hook PN 136	