

FIBERGLASS WITH GRAPHITE COATED BLANKET



“Green Arrow” FIBERGLASS WITH GRAPHITE COATED BLANKET

CODE	Description	Thickness	Max Temperature	Length of Roll
AB/NF/FGgraph	Fiberglass Fabric with Graphite Coating	0.8 mm	1200 °C	50 Meters x 1 Meter Wide
AB/NF/FGgraph	Fiberglass Fabric with Graphite Coating	1.2 mm	1200 °C	50 Meters x 1 Meter Wide
AB/NF/FGgraph	Fiberglass Fabric with Graphite Coating	1.7 mm	1200 °C	50 Meters x 1 Meter Wide

Characteristics: Fiberglass fabrics, when impregnated with graphite dispersant, results in high temperature flammability and adds high abrasion resistance to the fabric. It absorbs the molten welding splatters. The graphite depressant does not allow the fabric to swell, stretch or shrink chemically

 **A.B.C. BROTHERS TECH (I) PRIVATE LIMITED**

“ABC HOUSE” 14/15, Shivam Estate, Nr. Ujala Circle, B/h. SBI & Deepkamal Bajaj, S. G. Highway, Sarkhej, AHMEDABAD-382210. GUJARAT, INDIA
☎ +91 79 2689 0331 / 4 / 9 📠 +91 99099 88233, +91 99099 88198 / 7 / 6 📧 info@abcbrothers.in 🌐 www.abcbrothers.in